



# TAPKING™ SD

## MASONRY SCREWS / DURABLECOAT

### TESTED FOR USE IN

- Poured Concrete
- Grout Filled Masonry
- Hollow Masonry Substrate

**MIAMI-DADE COUNTY**  
**APPROVED**  
 NOA 23-0724.27

**Expiration Date:** June 27, 2024  
**Approval Date:** August 03, 2023

This product is approved and has been designed to comply with the Florida Building Code, including the high Velocity Hurricane Zone.

BBI#	DIAMETER	LENGTH	DESCRIPTION
660010	3/16"	1-1/4"	INDENT HWH SLOT
660015	3/16"	1-3/4"	INDENT HWH SLOT
660020	3/16"	2-1/4"	INDENT HWH SLOT
660025	3/16"	2-3/4"	INDENT HWH SLOT
660030	3/16"	3-1/4"	INDENT HWH SLOT
660035	3/16"	4"	INDENT HWH SLOT
660050	1/4"	1-1/4"	INDENT HWH SLOT
660055	1/4"	1-3/4"	INDENT HWH SLOT
660060	1/4"	2-1/4"	INDENT HWH SLOT
660070	1/4"	2-3/4"	INDENT HWH SLOT
660080	1/4"	3-1/4"	INDENT HWH SLOT
660090	1/4"	4"	INDENT HWH SLOT
660100	1/4"	5"	INDENT HWH SLOT
660110	1/4"	6"	INDENT HWH SLOT
660200	3/16"	1-1/4"	FLAT HEAD PHIL
660210	3/16"	1-3/4"	FLAT HEAD PHIL
660220	3/16"	2-1/4"	FLAT HEAD PHIL
660230	3/16"	2-3/4"	FLAT HEAD PHIL
660240	3/16"	3-1/4"	FLAT HEAD PHIL
660245	3/16"	3-3/4"	FLAT HEAD PHIL
660250	3/16"	4"	FLAT HEAD PHIL
660260	1/4"	1-1/4"	FLAT HEAD PHIL
660270	1/4"	1-3/4"	FLAT HEAD PHIL
660280	1/4"	2-1/4"	FLAT HEAD PHIL
660290	1/4"	2-3/4"	FLAT HEAD PHIL
660300	1/4"	3-1/4"	FLAT HEAD PHIL
660310	1/4"	4"	FLAT HEAD PHIL
660320	1/4"	5"	FLAT HEAD PHIL
660330	1/4"	6"	FLAT HEAD PHIL

**DON'T FORGET THE TAPKING™ DRILL BITS**



## BRIGHTON-BEST INTERNATIONAL

[www.brightonBEST.com](http://www.brightonBEST.com)

1 - 8 0 0 - 2 7 5 - 0 0 5 0



**WE CARRY A FULL LINE OF CARBIDE DRILL BITS**



# TAPKING™ SD

## MASONRY SCREWS / DURABLECOAT

### TESTED FOR USE IN

- Poured Concrete
- Grout Filled Masonry
- Hollow Masonry Substrate

### MIAMI-DADE COUNTY

**APPROVED**

NOA 23-0724.27

**Expiration Date:** June 27, 2024

**Approval Date:** August 03, 2023

This product is approved and has been designed to comply with the Florida Building Code, including the high Velocity Hurricane Zone.



### PHILLIPS TRIM HEAD SCREWS



BBI#	DIAMETER	LENGTH	FINISH
660410	1/4"	1-3/4"	WHITE, DURABLECOAT
660420	1/4"	2-1/4"	WHITE, DURABLECOAT
660430	1/4"	2-3/4"	WHITE, DURABLECOAT
660440	1/4"	3-1/4"	WHITE, DURABLECOAT
660450	1/4"	3-3/4"	WHITE, DURABLECOAT
660460	1/4"	4"	WHITE, DURABLE COAT
660610	1/4"	1-3/4"	BRONZE, DURABLECOAT
660620	1/4"	2-1/4"	BRONZE, DURABLECOAT
660630	1/4"	2-3/4"	BRONZE, DURABLECOAT
660640	1/4"	3-1/4"	BRONZE, DURABLECOAT
660650	1/4"	3-3/4"	BRONZE, DURABLECOAT
660660	1/4"	4"	BRONZE, DURABLECOAT
660810	1/4"	1-3/4"	SILVER, DURABLECOAT
660820	1/4"	2-1/4"	SILVER, DURABLECOAT
660830	1/4"	2-3/4"	SILVER, DURABLECOAT
660840	1/4"	3-1/4"	SILVER, DURABLECOAT
660850	1/4"	3-3/4"	SILVER, DURABLECOAT
660860	1/4"	4"	SILVER, DURABLECOAT

**DON'T FORGET THE TAPKING™ DRILL BITS**

WHITE

BRONZE

SILVER

WE CARRY A FULL LINE OF CARBIDE DRILL BITS



**BRIGHTON-BEST INTERNATIONAL**

www.brightonBEST.com

1 - 8 0 0 - 2 7 5 - 0 0 5 0





# TAPKING<sup>TM</sup> SD

## FREQUENTLY ASKED QUESTIONS

**Q.** What type of product is Taping SD?

**A.** Smaller diameter concrete screw for light duty applications.

**Q.** How does it work?

**A.** A pilot hole is drilled into substrate to a specific depth followed by insertion of Taping concrete screw set with screw gun or drill.

**Q.** What is the design of the Taping SD concrete screw?

**A.** Steel Fastener with spiral threads in either hex or flat head profiles designed to cut into drilled hole.

**Q.** Is the Taping SD removable?

**A.** Yes! Limited to only several additional installations.

**Q.** What type of carbide bits are suitable for Taping SD screws?

**A.** Standard ANSI SDS or straight shank carbide.

**Q.** What is the standard coating for the Taping SD?

**A.** Durablecoat blue coating for corrosion protection.

**Q.** What code approval is associated with the Taping SD?

**A.** Miami Dade County – NOA-23-0724.27

**Q.** What are the suitable substrates for Taping SD?

**A.** Concrete – hollow and solid block, brick and motor joints.

**Q.** Is the Taping SD suitable for fastening near an edge or when spacing is limited?

**A.** Yes! Less stress is applied to substrate via undercutting process.

**Q.** What is the size range?

**A.** 3/16" x 1 1/4" indent HWH & Flat Head blue through 4" in length.  
1/4" x 1 1/4" indent HWH & Flat Head blue through 6" in length.

**Q.** Is there a concrete screw offered for installation of hurricane shutters?

**A.** Yes! It is called Taping SD Trim Head series.

**Q.** Are there color coated Trim Head concrete screws available to match various hurricane window hardware?

**A.** Yes! They are available in White-Bronze and Silver colors.

**Q.** How are the Taping SD packaged?

**A.** They are available in 100 pieces/box and bulk boxes.

**Q.** What is the BBI family code for the Taping SD line.

**A.** 660

**Q.** Is the Taping SD Data and approvals posted on the BBI site?

**A.** Yes! Under catalogs and certificates.

**Q.** Is there a sell sheet available for the Taping SD product line?

**A.** Yes! It contains features and benefits along with dimensions.

**Q.** Are there installation instructions available for the Taping SD?

**A.** Yes! Instructions are included in each box.

**Q.** Is there technical assistance available?

**A.** Yes! Please e-mail us at [usanchor@brightonbest.com](mailto:usanchor@brightonbest.com).

