

Proferred VENDING SOLUTIONS

- 24/7 access to mission critical items
- Eliminate stock out's and excess inventory
- 20-30% Consumption reduction on average
- · Simple web-based software that can be easily accessed via computer or tablet
- Ability to restrict or limit products by employee or department
- Automated usage and transaction reports
- Drives savings and increased productivity





	Proferred [®] C3 Coil	Proferred [®] C5 Coil
Standard	Internal LED lighting	Internal LED lighting
Standard	10.1" Touchscreen Display	10.1" Touchscreen Display
Standard	Proximity Card Reader	Proximity Card Reader
Option: Barcode Reader	Additional Cost	Additional Cost
Cellular Services	Standard Cellular Connection via	Standard Cellular Connection via
	T-Mobile / Standard (no additional Cost)	T-Mobile / Standard (no additional Cost)
# of Items	Up to 43 Items	Up to 60 Items
Electrical Requirements	USA: 115VAC / 60Hz, 1.2 AMPS.	USA: 115VAC / 60Hz, 1.2 AMPS.
	International: 230VAC / 50Hz,	International: 230VAC / 50Hz,
	0.6 AMPS	0.6 AMPS
Connections	LAN / WIFI / Cellular Connection	LAN / WIFI / Cellular Connection
Height	72" (183 cm)	72" (183 cm)
Width	29.3" (74.4 cm)	41" (104 cm)
Depth	35.2" (89.4 cm)	35.2" (89.4 cm)
Weight	445 LB (202 KG)	628 LB (284 KG)

C3 Coil



Adjustable Locker

C5 Coil

	222
+	
LIME	
	-
SM Time Salaban Salaban	

Adjustable Locker Satellite

	Proferred [®] Locker Host	Proferred [®] Locker Satellite
Standard	Internal LED lighting	Internal LED lighting
Standard	10.1" Touchscreen Display	Connection via Host machine
Standard	Proximity Card Reader	NA
Option: Barcode Reader	Additional Cost	NA
Option: Powered Locker	Additional Cost	Additional Cost
(Adjustable Locker)		
Cellular Services	Standard Cellular Connection via	NA
	T-Mobile / Standard (no additional Cost)	
# of Doors	18 Doors Adjustable	20 Doors Adjustable
Electrical Requirements	USA: 115VAC / 60Hz, 1.0 AMPS.	USA: 115VAC / 60Hz, 1.0 AMPS.
	International: 230VAC / 50Hz,	International: 230VAC / 50Hz,
	0.5 AMPS	0.5 AMPS
Connections	LAN / WIFI / Cellular Connection	Connection via Host machine
Height	72" (183 cm)	72" (183 cm)
Width	30.25" (76 cm)	30.25" (76 cm)
Depth	24.5: (62cm)	24.5: (62cm)
Weight	357 LB (162 KG)	357 LB (162 KG)











