



TAP KING™ HD SS

CONCRETE SCREW ANCHOR

PATENTED TRIPLE THREAD



STABILIZES INSTALLATION



BBI#	SIZE	DRILL BIT DIA.	MIN. HOLE DEPTH SHALLOW	MIN. HOLE DEPTH DEEP	NOMINAL EMBEDMENT SHALLOW	NOMINAL EMBEDMENT DEEP	MAX. TORQUE SHALLOW	MAX. TORQUE DEEP
F60064*	1/4"x3"	1/4"	2 3/8	-	2	-	10	-
F60065*	1/4"x4"	1/4"	2 3/8	3 3/8	2	3	10	10
F60103	3/8"x3"	3/8"	3	-	2 3/4	-	35	-
F60104	3/8"x4"	3/8"	3	-	2 3/4	-	35	-
F60105	3/8"x5"	3/8"	3	4 1/4	2 3/4	4	35	35
F60106	3/8"x6"	3/8"	3	4 1/4	2 3/4	4	35	35
F60123	1/2"x4"	1/2"	3 3/8	-	3	-	35	-
F60124	1/2"x5"	1/2"	3 3/8	-	3	-	35	-
F60125	1/2"x6"	1/2"	3 3/8	5 3/8	3	5	35	35
F60127	1/2"x8"	1/2"	3 5/8	5 3/8	3	5	35	35

*Uncracked concrete only

BBI#	SIZE	WRENCH SIZE	MAX FIXTURE THICKNESS SHALLOW	MAX FIXTURE THICKNESS DEEP
F60064*	1/4"x3"	7/16	1"	-
F60065*	1/4"x4"	7/16	2"	1"
F60103	3/8"x3"	9/16	1/4"	-
F60104	3/8"x4"	9/16	1 1/4"	-
F60105	3/8"x5"	9/16	2 1/4"	1"
F60106	3/8"x6"	9/16	3 1/4"	2"
F60123	1/2"x4"	3/4	1"	-
F60124	1/2"x5"	3/4	2"	-
F60125	1/2"x6"	3/4	3"	1"
F60127	1/2"x8"	3/4	5"	3"



ICC-ES 4557

Cracked & Uncracked Concrete

APPROVED FOR USE IN

Static, Wind, & Seismic

CODE LISTED

IBC/IRC In Accordance with ICC-ES AC 193 & ACI 355.2

CODE COMPLIANCE

IBC 2021, 2018, 2015, 2013, 2009
IRC 2021, 2018, 2015, 2013, 2009

LABC 2023
LARC 2023
CBC 2022
CRC 2022
FBC 2023

316 STAINLESS STEEL



BRIGHTON-BEST INTERNATIONAL

www.brightonBEST.com

1 - 8 0 0 - 2 7 5 - 0 0 5 0

WE CARRY A FULL RANGE OF SDS PLUS & MAX CARBIDE BITS