



# TAP KING<sup>TM</sup> HD SS

## CONCRETE SCREW ANCHOR

PATENTED TRIPLE THREAD



| BBI#    | SIZE    | DRILL BIT DIA. | MIN. HOLE DEPTH SHALLOW | MIN. HOLE DEPTH DEEP | NOMINAL EMBEDMENT SHALLOW | NOMINAL EMBEDMENT DEEP | MAX. TORQUE SHALLOW | MAX. TORQUE DEEP |
|---------|---------|----------------|-------------------------|----------------------|---------------------------|------------------------|---------------------|------------------|
| F60064* | 1/4"x3" | 1/4"           | 2 3/8                   | -                    | 2                         | -                      | 10                  | -                |
| F60065* | 1/4"x4" | 1/4"           | 2 3/8                   | 3 3/8                | 2                         | 3                      | 10                  | 10               |
| F60103  | 3/8"x3" | 3/8"           | 3                       | -                    | 2 3/4                     | -                      | 35                  | -                |
| F60104  | 3/8"x4" | 3/8"           | 3                       | -                    | 2 3/4                     | -                      | 35                  | -                |
| F60105  | 3/8"x5" | 3/8"           | 3                       | 4 1/4                | 2 3/4                     | 4                      | 35                  | 35               |
| F60106  | 3/8"x6" | 3/8"           | 3                       | 4 1/4                | 2 3/4                     | 4                      | 35                  | 35               |
| F60123  | 1/2"x4" | 1/2"           | 3 3/8                   | -                    | 3                         | -                      | 35                  | -                |
| F60124  | 1/2"x5" | 1/2"           | 3 3/8                   | -                    | 3                         | -                      | 35                  | -                |
| F60125  | 1/2"x6" | 1/2"           | 3 3/8                   | 5 3/8                | 3                         | 5                      | 35                  | 35               |
| F60127  | 1/2"x8" | 1/2"           | 3 5/8                   | 5 3/8                | 3                         | 5                      | 35                  | 35               |

\* Uncracked concrete only

| BBI#    | SIZE    | WRENCH SIZE | MAX FIXTURE THICKNESS SHALLOW | MAX FIXTURE THICKNESS DEEP |
|---------|---------|-------------|-------------------------------|----------------------------|
| F60064* | 1/4"x3" | 7/16        | 1"                            | -                          |
| F60065* | 1/4"x4" | 7/16        | 2"                            | 1"                         |
| F60103  | 3/8"x3" | 9/16        | 1 1/4"                        | -                          |
| F60104  | 3/8"x4" | 9/16        | 1 1/4"                        | -                          |
| F60105  | 3/8"x5" | 9/16        | 2 1/4"                        | 1"                         |
| F60106  | 3/8"x6" | 9/16        | 3 1/4"                        | 2"                         |
| F60123  | 1/2"x4" | 3/4         | 1"                            | -                          |
| F60124  | 1/2"x5" | 3/4         | 2"                            | -                          |
| F60125  | 1/2"x6" | 3/4         | 3"                            | 1"                         |
| F60127  | 1/2"x8" | 3/4         | 5"                            | 3"                         |



ICC-ES 4557

Cracked & Uncracked Concrete

APPROVED FOR USE IN

Static, Wind, & Seismic

CODE LISTED

IBC/IRC In Accordance with ICC-ES AC 193 & ACI 355.2

CODE COMPLIANCE

IBC 2021, 2018, 2015, 2013, 2009  
IRC 2021, 2018, 2015, 2013, 2009

LABC 2023  
LARC 2023  
CBC 2022  
CRC 2022  
FBC 2023

316  
STAINLESS  
STEEL



## BRIGHTON-BEST INTERNATIONAL

www.brightonBEST.com

1 - 8 0 0 - 2 7 5 - 0 0 5 0

WE CARRY  
A FULL  
RANGE OF  
SDS PLUS &  
MAX CARBIDE  
BITS