



# TAPKING<sup>TM</sup> SD

## MASONRY SCREWS / DURABLECOAT

### TESTED FOR USE IN

- Poured Concrete
- Grout Filled Masonry
- Hollow Masonry Substrate

MIAMI-DADE COUNTY

APPROVED

NOA 24-0424.05

**Expiration Date:** June 27, 2029

**Approval Date:** May 23, 2024

This product is approved and has been designed to comply with the Florida Building Code, including the high Velocity Hurricane Zone.

BBI#	DIAMETER	LENGTH	DESCRIPTION
660010	3/16"	1-1/4"	INDENT HWH SLOT
660015	3/16"	1-3/4"	INDENT HWH SLOT
660020	3/16"	2-1/4"	INDENT HWH SLOT
660025	3/16"	2-3/4"	INDENT HWH SLOT
660030	3/16"	3-1/4"	INDENT HWH SLOT
660035	3/16"	4"	INDENT HWH SLOT
660050	1/4"	1-1/4"	INDENT HWH SLOT
660055	1/4"	1-3/4"	INDENT HWH SLOT
660060	1/4"	2-1/4"	INDENT HWH SLOT
660070	1/4"	2-3/4"	INDENT HWH SLOT
660080	1/4"	3-1/4"	INDENT HWH SLOT
660090	1/4"	4"	INDENT HWH SLOT
660100	1/4"	5"	INDENT HWH SLOT
660110	1/4"	6"	INDENT HWH SLOT
660200	3/16"	1-1/4"	FLAT HEAD PHIL
660210	3/16"	1-3/4"	FLAT HEAD PHIL
660220	3/16"	2-1/4"	FLAT HEAD PHIL
660230	3/16"	2-3/4"	FLAT HEAD PHIL
660240	3/16"	3-1/4"	FLAT HEAD PHIL
660245	3/16"	3-3/4"	FLAT HEAD PHIL
660250	3/16"	4"	FLAT HEAD PHIL
660260	1/4"	1-1/4"	FLAT HEAD PHIL
660270	1/4"	1-3/4"	FLAT HEAD PHIL
660280	1/4"	2-1/4"	FLAT HEAD PHIL
660290	1/4"	2-3/4"	FLAT HEAD PHIL
660300	1/4"	3-1/4"	FLAT HEAD PHIL
660310	1/4"	4"	FLAT HEAD PHIL
660320	1/4"	5"	FLAT HEAD PHIL
660330	1/4"	6"	FLAT HEAD PHIL

**DON'T FORGET THE TAPKING<sup>TM</sup> DRILL BITS**



## BRIGHTON-BEST INTERNATIONAL

[www.brightonBEST.com](http://www.brightonBEST.com)

1 - 8 0 0 - 2 7 5 - 0 0 5 0



WE CARRY A  
FULL LINE  
OF CARBIDE  
DRILL BITS





# TAPKING™ SD

## MASONRY SCREWS / DURABLECOAT

### TESTED FOR USE IN

- Poured Concrete
- Grout Filled Masonry
- Hollow Masonry Substrate

**MIAMI-DADE COUNTY**

**APPROVED**

**NOA 24-0424.05**

**Expiration Date:** June 27, 2029

**Approval Date:** May 23, 2024

This product is approved and has been designed to comply with the Florida Building Code, including the high Velocity Hurricane Zone.



### PHILLIPS TRIM HEAD SCREWS



BBI#	DIAMETER	LENGTH	FINISH
660410	1/4"	1-3/4"	WHITE, DURABLECOAT
660420	1/4"	2-1/4"	WHITE, DURABLECOAT
660430	1/4"	2-3/4"	WHITE, DURABLECOAT
660440	1/4"	3-1/4"	WHITE, DURABLECOAT
660450	1/4"	3-3/4"	WHITE, DURABLECOAT
660460	1/4"	4"	WHITE, DURABLE COAT
660610	1/4"	1-3/4"	BRONZE, DURABLECOAT
660620	1/4"	2-1/4"	BRONZE, DURABLECOAT
660630	1/4"	2-3/4"	BRONZE, DURABLECOAT
660640	1/4"	3-1/4"	BRONZE, DURABLECOAT
660650	1/4"	3-3/4"	BRONZE, DURABLECOAT
660660	1/4"	4"	BRONZE, DURABLECOAT
660810	1/4"	1-3/4"	SILVER, DURABLECOAT
660820	1/4"	2-1/4"	SILVER, DURABLECOAT
660830	1/4"	2-3/4"	SILVER, DURABLECOAT
660840	1/4"	3-1/4"	SILVER, DURABLECOAT
660850	1/4"	3-3/4"	SILVER, DURABLECOAT
660860	1/4"	4"	SILVER, DURABLECOAT

**DON'T FORGET THE TAPKING™ DRILL BITS**

**WHITE**

**BRONZE**

**SILVER**

**WE CARRY A  
FULL LINE  
OF CARBIDE  
DRILL BITS**



## BRIGHTON-BEST INTERNATIONAL

[www.brightonBEST.com](http://www.brightonBEST.com)

1 - 8 0 0 - 2 7 5 - 0 0 5 0



BBI products and services offered exclusively through distribution ©2019 Brighton-Best International, Inc.



# TAPKING<sup>TM</sup> SD

## FREQUENTLY ASKED QUESTIONS

**Q. What type of product is Taping SD?**

A. Smaller diameter concrete screw for light duty applications.

**Q. How does it work?**

A. A pilot hole is drilled into substrate to a specific depth followed by insertion of Taping concrete screw set with screw gun or drill.

**Q. What is the design of the Taping SD concrete screw?**

A. Steel Fastener with spiral threads in either hex or flat head profiles designed to cut into drilled hole.

**Q. Is the Taping SD removable?**

A. Yes! Limited to only several additional installations.

**Q. What type of carbide bits are suitable for Taping SD screws?**

A. Standard ANSI SDS or straight shank carbide.

**Q. What is the standard coating for the Taping SD?**

A. Durablecoat blue coating for corrosion protection.

**Q. What code approval is associated with the Taping SD?**

A. Miami Dade County – NOA 24-0424.05

**Q. What are the suitable substrates for Taping SD?**

A. Concrete – hollow and solid block, brick and mortar joints.

**Q. Is the Taping SD suitable for fastening near an edge or when spacing is limited?**

A. Yes! Less stress is applied to substrate via undercutting process.

**Q. What is the size range?**

A. 3/16" x 1 1/4" indent HWH & Flat Head blue through 4" in length.  
1/4" x 1 1/4" indent HWH & Flat Head blue through 6" in length.

**Q. Is there a concrete screw offered for installation of hurricane shutters?**

A. Yes! It is called Taping SD Trim Head series.

**Q. Are there color coated Trim Head concrete screws available to match various hurricane window hardware?**

A. Yes! They are available in White-Bronze and Silver colors.

**Q. How are the Taping SD packaged?**

A. They are available in 100 pieces/box and bulk boxes.

**Q. What is the BBI family code for the Taping SD line.**

A. 660

**Q. Is the Taping SD Data and approvals posted on the BBI site?**

A. Yes! Under catalogs and certificates.

**Q. Is there a sell sheet available for the Taping SD product line?**

A. Yes! It contains features and benefits along with dimensions.

**Q. Are there installation instructions available for the Taping SD?**

A. Yes! Instructions are included in each box.

**Q. Is there technical assistance available?**

A. Yes! Please e-mail us at [usanchor@brightonbest.com](mailto:usanchor@brightonbest.com).

